

Course No.			Consult No.	Print to the state of the state	they disperse replace thank trans-continued and the second and the
1	165.00'	S 0° 11' 25" E	17	165.06	S 0° 01' 33" E
2	165.26'	S 89° 43' 45" E	18	495.06	S 89° 43' 31" E
3	2 32.63'	N 45° 05 32" E	19	52265	S 18° 22' 26" E
4	<b>33</b> 0.56'	S 89° 43' 49" E	20	330.17	S 0° 01' 53" W
5 .	495.03	S 0° 09' 50" E	21	595.61	S 56° 03' 09" E
6	234.39	S 44°58' 39" E	22	494.32	S 0° 04' 12" W
7	495.61	S 89° 43′ 35″ E	23	232.26	S 45° 12' 21" W
8	330.05	S 0° 08' 15" E	24	677.74	S 14° 06' 01" W
9	495.49	S 89°43' 26' E	25	680.24	S 13° 56' 04" E
10	825,16	N 0° 07' 04" W	26	658.77	S 0° 03' 25" W
11	232.78	N 45° 07' 06" E			- 127
12	165.28 <sup>1</sup>	S 89° 43′ 49" E			
13 `	597.06'	S 33° 42' 27" E			
14	495.41	S 89° 43' 39" E			
15	165.05	S 0° 03' 33" E			
16	495.17	S 89° 43' 35" E			

Mook No. E-1030 Date September, 1965

i, Herman E. Smith, a Ringleholad Professional Engineer, the Bindby certify that the blove plat is a true and recently survivor of Sec. 9 , 110 V F18 E as made under my supervision.

Hermont. Smith

## OKLAHOMA CERTIFIED CORNER RECORD

Existing Obliterated Lost	C. M. Docu	ment No.
CORNER DESCRIPTION:		• CORNER MONUMENT
W <sup>1</sup> / <sub>4</sub> Corner of Section 9 Township 10 North	Range 18 East	
Meridian I.B.&M. County McIntosh County	, nonge	
DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES AND RESTORATION: (Give Sources of Information)	ANY SUBSECUENT	
	·	
MONUMENT DESCRIPTION:  Description of Corner Evidence Found:		
EXISTING 3/4" IRON PIN		
EXISTING 14 TROPO PING	<del></del>	
Description of Corner Evidence Set:		
NONE		
REFERENCE MEASUREMENTS: (At Least Three)	Distance	Bearing
Description	Feet activations	True $\square$ Magnetic $ u$
Set 60d Nail in 10" Elm Tree Set 60d Nail in 15" Hickory	25.35 30.40	n 30° w s 40° e
Set 60d Nail in 7" Elm	10.36	s 40° W
STATEMENT OF METHOD USED TO DETERMINE CORNER LOCATION	IN: (Lost Corners Only)	
	RVEYOR'S CERTIFICATION numents and accessories ind	
† de:	scribed and shown. I further ge re checked for any filings prior	rtify that the corner record
-60d CALV. N -IN 10" ELM ? 13	The checked right any minings pylor	()
3/6	TOM OFF	Juna )
	iffman Surveying Compa	my, Inc.
60	00 Emporia St., Suite eet Address/Post Office Box	"C"
	iskogee, Oklahoma 7440	01
NAIL IN 15" X	iceember 18,1986	L.S. 1020
N 7" ELM	te and Registration Number	LAKD
OKLAHOMA STATE PLANE COORDINATES: (If Determined)		FARMER
<: Y: ZONE:		RON HUFFMAN
Accepted and Filed:		L.S. 1020
Archivist, Archives & Records Division Oklahoma Department of Libraries		No.
		ON LABOR TO

OKLAHOMA CERTIFI	ED CORNER RECORD	
ExistingObliteratedLost	C. M. Document No	
CORNER DESCRIPTION:	• CORNER	R MONUMENT
SW Corner of Section 9 Township 10 North	Pages 18 East	
Meridian I.B.&M County Mc Intosh		
DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES RESTORATION: (Give Sources of Information) GLO NOTES:		
Set a sandstone 24x14x5", 18" in the ground, Black Oak, 14" in diameter, N 59° E, 50 links Black Oak, 14" in diameter, S 32° E, 52 links Red Oak, 18" in diameter, S 30° W, 97 Links Red Oak, 20" in diameter, N 88° W, 75 links  MONUMENT DESCRIPTION:  Description of Corner Evidence Found:	marked 4 notches on S and E. edges distance distance distance distance distance	· ·
EXIST, #4 PEBAR		•
Description of Corner Evidence Set:		
NONE		
-		
REFERENCE MEASUREMENTS: (At Least Three)	Distance	Bearing
- Description		Magnetic 💆
Existing $60d$ Nail in 48" post oak, east face Set $60d$ Nail in corner post Existing $60d$ Nail in corner post	3.98 Sou	0° W th 0° W
STATEMENT OF METHOD USED TO DETERMINE CORNER LO	CATION: (Lost Corners Only)	
•		
SKETCH:  (IST. GOC! NAIL  COR. POST  THOSE  EXIST. #4 PEEAR  1786.	SURVEYOR'S CERTIFICATION: This is to monuments and accessories indicated above described and shown. I further certify that the were checked for any filings prior to making the Signature  Huffman Surveying Company, Inc.  Firm  600 Emporia St., Suite "C"  Street Address/Post Office Box	re are correctly se corner records
30 00 X X X X X X X X X X X X X X X X X	Muskogee, Oklahoma 74401 City, State, and Zip Code	s. 1020

EXFST. GOD NAIL IN 48" POST OAK OKLAHOMA STATE PLANE COORDINATES: (If Determined) X:\_\_\_\_\_ Y:\_\_\_\_ ZONE:\_

Accepted and Filed: Archivist, Archives & Records Division

Date:\_\_\_

Oklahoma Department of Libraries 200 Northeast 18th Street Oklahoma City, Oklahoma 73105



## OKLAHOMA CERTIFIED CORNER RECORD

Existing Obliterated Lost	C. M. Docum	ent No
CORNER DESCRIPTION:		CORNER MONUMENT
E <sup>1</sup> 4 Corner of Section 9 Township 10 North	Range <u>18 East</u>	
Meridian B.&M. County McIntosh		
DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES RESTORATION: (Give Sources of Information)	AND ANY SUBSEQUENT	
N/A		
<i>f</i>		
MONUMENT DECORIGEION.		
MONUMENT DESCRIPTION:  Description of Corner Evidence Found:		
EXIST. # 6 REBAR		•
·	•	
Description of Corner Evidence Set:		
MONE		
	N.	
<del>.</del> :	<b>D</b> .	Bearing
REFERENCE MEASUREMENTS: (At Least Three)  Description	Distance Feet	True Magnetic
Set 60d Nail in 15" Hickory	30.40	S 40° E
Set 60 <u>d</u> Nail in 7" Elm Set 60 <u>d</u> Nail in 10" Elm	10.36 25.35	S 40° W N 30° W
	; <del> 175</del>	1 30 H
STATEMENT OF METHOD USED TO DETERMINE CORNER LOC	CATION: (Lost Corners Only)	
		•
SKETCH:	SURVEYOR'S CERTIFICATION: monuments and accessories indi	
Q	described and shown. I further cer	tify that the corner records
ET GOD GALV. IL INIO"ELM T	were checked for any filings prior t	o making this survey. 7
	Kon Sury	yan)
SEXIST. 46 REBAR	Signature Huffman Surveying Compan	y, Inc.
	Firm 600 Emporia St., P.O. Bo	
30,400	Street Address/Post Office Box Muskogee, Oklahoma 74402	
3/03	City, State and Zip Code	
SET GOD NAIL SET GOD NAIL IN 15" HICKORY	Date and Registration Number	LS.1020
SET GOD NAIL IN 7" ELM  SET GOD NAIL IN 15" HICKORY		
OKLAHOMA STATE PLANE COORDINATES: (If Determined)		AL
X: Y: ZONE:		RON
Accepted and Filed:		HUFFMAN L.S. 1020
Archivist, Archives & Records Division Oklahoma Department of Libraries		
200 Northeast 18th Street		CALLING THE STATE OF THE STATE
Date: Oklahoma City, Oklahoma 73105		Adopted 12:1/78